



Product Data

## Hyspin AWH-M (Superclean)

High viscosity index anti-wear hydraulic oils

### Description

The Castrol Hyspin™ AWH-M (Superclean) hydraulic oil is a shear stable high viscosity index lubricant are based on the latest stabilized zinc additive technology and filtered to ISO class 15/13/10.

### Application

Hyspin AWH-M contains a shear stable additive system which helps maintain the viscosity characteristics of the product over a wide temperature range, even during prolonged use, and imparts a very low pour point which enables the product to be used in very cold environments. It exhibits excellent corrosion and wear protection as well as outstanding thermal and oxidative stability. In addition, Hyspin AWH-M has excellent hydrolytic stability and separates rapidly from water contamination upon standing. Applications include:

- Outdoor equipment which are likely to operate in wide temperature ranges, such as machinery subjected to cold start up conditions and high temperature continuous running. Examples include off-highway and marine applications.
- Indoor manufacturing equipment that incorporates control systems requiring minimal viscosity change with temperature. Examples include precision machine tools..
- The Hyspin AWH-M range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers..

Hyspin AWH-M is classified as follows: DIN 51502 classification – HVLP  
ISO 6743/4 - Hydraulic Oils Type HV

Hyspin AWH-M grades meet the requirements (for appropriate viscosity grade) of:

DIN 51524 Part 3

Cincinnati Lamb (Milacron) P 68

Denison (Parker Hannafin) HF-0

US Steel 126 & 127

Eaton (formerly Vickers) I-286-S & M-2950-S

Bosch Rexroth RE90220

### Advantages

- High viscosity index and low pour point enables the product to be used over a wide temperature range, with good shear stability which means no excessive loss in viscosity due to mechanical shearing.
- Excellent anti-wear performance provides extended wear protection for hydraulic pumps. Reduced down time due to unscheduled maintenance and savings from replacement part costs.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.
- Good filterability gives a cleaner system with less frequent filter changes.

## Typical Characteristics

Name	Method	Units	Hyspin AWH-M 32 Superclean
ISO Viscosity Grade	-	-	32
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m³	880
Base Oil Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm²/s	32
Base Oil Viscosity @ 100°C / 212°F	ISO 3104 / ASTM D445	mm²/s	6.41
Viscosity Index	ISO 2909 / ASTM D2270	-	>150
Pour Point	ISO 3016 / ASTM D97	°C/°F	-45/-49
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	210/411
Flash Point - closed cup method	ISO 2719 / ASTM D93	°C/°F	200/392
Foam Sequence I - tendency / stability	ISO 6247 / ASTM D892	ml/ml	20/0
Water Separation @ 54°C / 129°F (40/37/3)	ISO 6614 / ASTM D1401	min	10
Air Release @ 50°C / 122°F	ISO 9120 / ASTM D3427	min	4
FZG Gear Scuffing test - A/8.3/90	ISO 14635-1	Failure Load Stage	11
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	-	Pass
Rust test - synthetic seawater (24 hrs)	ISO 7120 / ASTM D665B	-	Pass
Particle Count	ISO 4406	-	16/14/11

Subject to usual manufacturing tolerances.

Hyspin AWH-M (Superclean)

12 Jan 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600  
[www.castrol.com/en\\_us/b2b/home.html](http://www.castrol.com/en_us/b2b/home.html)