# SAFETY DATA SHEET



#### Castrol Transmax Dex III Multivehicle

# Section 1. Chemical product and company identification

GHS product identifier Castrol Transmax Dex III Multivehicle

**Product code** 467242-TR01 **SDS no.** 467242

Relevant identified uses of the substance or mixture and uses advised against

Product use Automatic transmission fluid

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

**Supplier** BP Petrolleri A.Ş.

Değirmen Yolu Cad. No:28 Kat: 3 Asya Ofis Park

34752 İçerenköy / Ataşehir, İstanbul

TURKEY

**EMERGENCY TELEPHONE** 

NUMBER

CASTROL DIRECT 0212 473 77 37 Carechem: +44 (0) 1235 239 670 (24/7)

Ministry of Health National Poison Information Centre: 114 (24 hours)

#### Section 2. Hazards identification

Classification of the Not classified.

substance or mixture

**GHS label elements** 

Signal word No signal word.

**Hazard statements** No known significant effects or critical hazards.

**Precautionary statements** 

PreventionNot applicable.ResponseNot applicable.StorageNot applicable.DisposalNot applicable.

Other hazards which do not

result in classification

Defatting to the skin.

# Section 3. Composition/information on ingredients

Substance/mixture Mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product name Castrol Transmax Dex III Multivehicle

**Version** 2.01 **Date of issue** 03/05/2021.

Product code 467242-TR01

Page: 1/8

Format Azerbaijan

Language ENGLISH

Azerbaijan

# Section 3. Composition/information on ingredients

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	≥50 - ≤75	64742-54-7
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥25 - ≤50	64742-65-0
2-Propenoic acid, 2-methyl-, butyl ester, polymer with N-[3-	≤3	176487-46-0
(dimethylamino)propyl]-2-methyl-2-propenamide, dodecyl 2-methyl-		
2-propenoate, eicosyl 2-methyl-2-propenoate, hexadecyl 2-methyl-		
2-propenoate and octadecyl 2-methyl-2-propenoate		
Distillates (petroleum), hydrotreated light paraffinic	≤3	64742-55-8
Bis (2-hydroxyethyl) tallow alkylamine	<0.25	61791-44-4
3-(isodecyloxy)propylamine	<0.1	30113-45-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

#### Section 4. First aid measures

#### **Description of necessary first aid measures**

**Inhalation** In case of inhalation of decomposition products in a fire, symptoms may be delayed.

If inhaled, remove to fresh air. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur.

**Ingestion** Do not induce vomiting unless directed to do so by medical personnel. Get medical

attention if symptoms occur.

**Skin contact** Wash skin thoroughly with soap and water or use recognised skin cleanser.

Remove contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention if symptoms occur.

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing.

Check for and remove any contact lenses. Get medical attention.

#### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

#### Indication of immediate medical attention and special treatment needed, if necessary

**Specific treatments** No specific treatment.

**Notes to physician** In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours. Treatment should in general be symptomatic and directed to relieving any effects.

**Protection of first-aiders**No action shall be taken involving any personal risk or without suitable training.

# Section 5. Firefighting measures

**Extinguishing media** 

Suitable extinguishing

media

Eye contact

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

**Unsuitable extinguishing** 

media

Do not use water jet.

Specific hazards arising

from the chemical

In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

Combustion products may include the following:

carbon oxides (CO, CO<sub>2</sub>) (carbon monoxide, carbon dioxide)

nitrogen oxides (NO, NO2 etc.)

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire. No action shall be taken involving any personal risk or without

suitable training.

**Product name** Castrol Transmax Dex III Multivehicle

Format Azerbaijan

Page: 2/8

**Version** 2.01 **Date of issue** 03/05/2021.

Language ENGLISH

Azerbaijan (ENGLISH)

Product code 467242-TR01

# Section 5. Firefighting measures

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

#### Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

#### **Precautions for safe handling**

Protective measures
Advice on general
occupational hygiene

Put on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Not suitable Prolonged exposure to elevated temperature

# Section 8. Exposure controls/personal protection

**Control parameters** 

Occupational exposure limits

None.

Product name Castrol Transmax Dex III Multivehicle

**Version** 2.01 **Date of issue** 03/05/2021.

Product code 467242-TR01

Page: 3/8

Format Azerbaijan

Language ENGLISH

**Azerbaijan** 

# Section 8. Exposure controls/personal protection

# Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

# **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

# Eye/face protection Skin protection Hand protection

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### **Body protection**

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

#### **Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Product name Castrol Transmax Dex III Multivehicle

Version 2.01 Date of issue 03/05/2021.

Product code 467242-TR01 Page: 4/8
Format Azerbaijan Language ENGLISH

**Azerbaijan** 

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** Liquid. Colour Red. [Light] **Odour** Not available. **Odour threshold** Not available. pН Not applicable. **Melting point** Not available. **Boiling point** Not available.

Open cup: 216°C (420.8°F) [Cleveland.] Flash point

**Evaporation rate** Not available.

Not applicable. Based on - Physical state Flammability (solid, gas)

Lower and upper explosive

(flammable) limits

Not available.

Vapour pressure Not available. Vapour density Not available. Relative density Not available.

**Density** 859 kg/m3 (0.859 g/cm3) at 15°C

insoluble in water. Solubility Partition coefficient: n-Not available.

octanol/water

Not available. **Auto-ignition temperature Decomposition temperature** Not available.

**Viscosity** Kinematic: 35 mm<sup>2</sup>/s (35 cSt) at 40°C

Kinematic: 7.2 mm<sup>2</sup>/s (7.2 cSt) at 100°C

## Section 10. Stability and reactivity

Reactivity No specific test data available for this product. Refer to Conditions to avoid and

Incompatible materials for additional information.

**Chemical stability** The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not

occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame).

**Incompatible materials** Reactive or incompatible with the following materials: oxidising materials.

**Hazardous decomposition** 

products

should not be produced.

Under normal conditions of storage and use, hazardous decomposition products

# **Section 11. Toxicological information**

#### Information on toxicological effects

#### **Aspiration hazard**

Name	Result
Distillates (petroleum), hydrotreated heavy paraffinic Distillates (petroleum), solvent-dewaxed heavy paraffinic Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Product name Castrol Transmax Dex III Multivehicle Product code 467242-TR01 Page: 5/8 Version 2.01 Date of issue 03/05/2021. Format Azerbaijan Language ENGLISH **Azerbaijan** (ENGLISH)

# **Section 11. Toxicological information**

Information on likely routes

of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

**Eye contact** No known significant effects or critical hazards.

**Inhalation** Exposure to decomposition products may cause a health hazard. Serious effects

may be delayed following exposure.

**Skin contact** Defatting to the skin. May cause skin dryness and irritation.

**Ingestion** No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data.

**Inhalation** May be harmful by inhalation if exposure to vapour, mists or fumes resulting from

thermal decomposition products occurs.

**Skin contact** Adverse symptoms may include the following:

irritation dryness cracking

**Ingestion** No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Eye contact** Potential risk of transient stinging or redness if accidental eye contact occurs.

**Skin contact** Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

**Ingestion** Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

GeneralNo known significant effects or critical hazards.CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

# Section 12. Ecological information

**Environmental effects** No known significant effects or critical hazards.

#### Persistence and degradability

Expected to be biodegradable.

#### **Bioaccumulative potential**

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

**Mobility** Spillages may penetrate the soil causing ground water contamination.

Other ecological information Spills may form a film on water surfaces causing physical damage to organisms.

Oxygen transfer could also be impaired.

Product name Castrol Transmax Dex III Multivehicle Product code 467242-TR01 Page: 6/8

Version 2.01 Date of issue 03/05/2021. Format Azerbaijan Language ENGLISH

Azerbaijan (ENGLISH)

# Section 12. Ecological information

### Section 13. Disposal considerations

**Disposal methods** 

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Not available. Special precautions for user

# Section 15. Regulatory information

Regulation according to other foreign laws

**REACH Status** For the REACH status of this product please consult your company contact, as

identified in Section 1.

**United States inventory** All components are active or exempted.

(TSCA 8b)

(TCSI)

**Australia inventory (AICS)** At least one component is not listed.

Canada inventory All components are listed or exempted. China inventory (IECSC) All components are listed or exempted.

Japan inventory (ENCS) At least one component is not listed. **Korea inventory (KECI)** All components are listed or exempted.

**Philippines inventory** All components are listed or exempted. (PICCS)

**Taiwan Chemical** All components are listed or exempted. **Substances Inventory** 

Product name Castrol Transmax Dex III Multivehicle

Page: 7/8 Version 2.01 Date of issue 03/05/2021. Format Azerbaijan Language ENGLISH

Product code 467242-TR01

**Azerbaijan** (ENGLISH)

# Section 15. Regulatory information

#### Section 16. Other information

#### **History**

Date of printing 3/5/2021

Date of issue/Date of 3/5/2021

revision

Date of previous issue 3/5/2021 Version 2.01

Prepared by Product Stewardship

Key to abbreviations ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation [Regulation (EC) No. 1907/2006]

**UN = United Nations** 

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0,

72623-87-1

References Not available.

Indicates information that has changed from previously issued version.

#### **Notice to reader**

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Castrol Transmax Dex III Multivehicle

**Version** 2.01 **Date of issue** 03/05/2021.

Product code 467242-TR01 Page: 8/8

Format Azerbaijan Language ENGLISH

**Azerbaijan**